


## X3高性能滚子链 X3 series high performance roller chains

DonghuaX<sup>3</sup>®系列高性能链条通过产品优化设计、采用先进制造工艺，并进行严格的质量控制。链条疲劳强度比ISO 606标准规定的同规格链条的疲劳强度提升60%以上，并提高了链条耐磨损性能。

DonghuaX<sup>3</sup>® series high performance roller chains are based on optimized design, advanced technology and excellent quality control, fatigue strength is 60 percent more than ISO 606 standard roller chain of the same specification, and the wear resistant is increased.



东华链号 Donghua Chain No.	节距	滚子直径	内节内宽	销轴直径	销轴长度		内链板高度	链板厚度	排距	抗拉强度	平均抗拉强度	每米长重
	Pitch	Roller diameter	Width between inner plates	Pin diameter	Pin length		Inner plate depth	Plate thickness	Transverse pitch	Tensile strength	Average tensile strength	Weight per meter
	P	d1 max	b1 min	d2 max	L max	Lc max	h2 max	t/T	Pt	Q min	Q0	q
	mm	mm	mm	mm	mm	mm	mm	mm	mm	kN/lbf	kN	kg/m
*06BX3-1	9.525	6.35	5.72	3.28	13.15	14.10	8.20	1.30	-	10.0/2248	11.00	0.43
08BX3-1	12.700	8.51	7.75	4.45	16.70	18.20	11.80	1.60	-	21.0/4721	23.10	0.74
10BX3-1	15.875	10.16	9.65	5.08	19.50	20.90	14.70	1.70	-	28.5/6407	31.35	1.00
12BX3-1	19.050	12.07	11.68	5.72	22.50	24.20	16.00	1.85	-	33.0/7418	36.30	1.23
16BX3-1	25.400	15.88	17.02	8.28	36.10	37.40	21.00	4.15/3.10	-	70.0/15736	77.00	2.90
20BX3-1	31.750	19.05	19.56	10.19	41.30	45.00	26.50	4.50/3.50	-	106.7/23986	117.37	3.96
24BX3-1	38.100	25.40	25.40	14.63	53.40	57.80	33.20	6.00/4.80	-	176.0/39565	193.60	7.60
28BX3-1	44.450	27.94	30.99	15.90	65.10	69.50	36.70	7.50/6.00	-	230.0/51704	253.00	9.10
32BX3-1	50.800	29.21	30.99	17.81	66.00	71.00	42.00	7.00/6.00	-	280.0/62944	308.00	10.97
06BX3-2	9.525	6.35	5.72	3.28	23.40	24.40	8.20	1.30	10.24	18.5/4159	20.35	0.82
08BX3-2	12.700	8.51	7.75	4.45	31.00	32.20	11.80	1.60	13.92	36.0/8093	39.60	1.43
10BX3-2	15.875	10.16	9.65	5.08	36.10	37.50	14.70	1.70	16.59	55.6/12499	61.16	1.97
12BX3-2	19.050	12.07	11.68	5.72	42.00	43.60	16.00	1.85	19.46	63.5/14275	69.85	2.47
16BX3-2	25.400	15.88	17.02	8.28	68.00	69.30	21.00	4.15/3.10	31.88	121.9/27403	134.09	5.80
20BX3-2	31.750	19.05	19.56	10.19	7.80	81.50	26.50	4.50/3.50	36.45	211.2/47478	232.32	7.70
24BX3-2	38.100	25.40	25.40	14.63	101.70	106.20	33.20	6.00/4.80	48.36	308.0/69238	338.80	14.34
28BX3-2	44.450	27.94	30.99	15.90	124.60	129.10	36.70	7.50/6.00	59.56	414.0/93067	455.40	17.76
32BX3-2	50.800	29.21	30.99	17.81	124.60	129.60	42.00	7.00/6.00	58.55	504.0/113299	554.40	22.47

\*直链板  
\*Straight side plates